



**webeye**<sup>TM</sup>

SECURITY  
SAFETY  
TECHNOLOGY  
INNOVATION

014:DNH SPECIFICATION SHEET

**DVR**



## W.E.A.S TVR 4CH

### 4 Channel webeye Alarm System TVR

- 4 Channels / TVI support coaxitron
- Support Dropbox and Google Drive
- 4 Alarm Inputs
- Supports No FIXED IP (P2P)
- Cloud storage
- Timeline Functionality

**T. Sales**

**UK** +44 (0)115 714 9990

**USA** (863) 588-3757

**Technical**

**UK** +44 (0)115 714 9999

**USA** (863) 588-3757

**E. UK** [sales@webeyecms.com](mailto:sales@webeyecms.com)

**USA** [paul.ellis@webeyecms.com](mailto:paul.ellis@webeyecms.com)

**W.** [www.webeyecms.com](http://www.webeyecms.com)

[www.webeyecorp.com](http://www.webeyecorp.com)

# W.E.A.S TVR 4CH

## 4 Channel webeye Alarm System TVR

|                      |                                                              |                     |                                                                            |
|----------------------|--------------------------------------------------------------|---------------------|----------------------------------------------------------------------------|
| Pentaplex Function   | Live monitoring, recording, playback, backup & remote access | Network functions   | DHCP, PPPOE, DDNS, SMTP, SNTP, FTP, UPnP, P2P                              |
| Video Input          | 4ch. BNC / TVI support coaxitron                             | Remote operation    | Monitoring, PTZ Control, Playback, System Setting, File Download, Log Info |
| Video Resolution     | D1/CIF/720P/1080P/WDI optional                               | Smart phone         | iPhone, iPad, Android                                                      |
| Video Output         | HDMI, VGA, BNC                                               | Hard Disk           | 1 SATA Port, SATA Supports 4TB                                             |
| Display Resolution   | 1080P(25/30fps), 720P(25/30/50/60fps),960H                   | USB Interface       | 2 USB 2.0 Ports                                                            |
| Audio Input          | 1 ch. RCA (Line in,2Vpp,1Kohms)                              | RS485               | Standard 485, Half Duplex, PTZ control                                     |
| Audio Output         | 1 RCA (Line out,2Vpp,300ohms)                                | Power Supply        | DC12V/1.5A                                                                 |
| Privacy Masking      | 4 zones                                                      | Power Consumption   | 8W (without HDD)                                                           |
| Motion Detection     | 396 (22x18) Detection Zone, Variable Sensitivity Levels      | Working environment | 0°C ~ +55°C / 10% – 90%RH                                                  |
| Alarm Inputs/Outputs | 4ch; 1ch. NO, NC                                             | Dimensions (W*D*H)  | 1U, 320x245x50 (mm)                                                        |
| Backup Methods       | USB, HDD, Network                                            | Weight              | 2Kg (without HDD)                                                          |
| Network protocol     | TCP/IP, UDP, HTTP, RTP/RTSP                                  |                     |                                                                            |

**T. Sales**

**UK** +44 (0)115 714 9990

**USA** (863) 588-3757

**Technical**

**UK** +44 (0)115 714 9999

**USA** (863) 588-3757

**E. UK** sales@vdomain.co.uk

**USA** paul.ellis@webeyecms.com

**W.** www.webeyecms.com

www.vdomain.co.uk

www.webeyecorp.com

